HDS 7/10-4 M

Medium class hot water pressure washer with a host of user-friendly features.













Order no.

1.077-901.0

- Axial pump with turbo blower
- Economical eco!efficiency mode
- SDS system

_		
Technical data		
EAN code		4054278140032
Current type	Ph / V / Hz	1 / 240 / 50
Flow Rate	l/h	350 - 700
Operating pressure	bar / MPa	30 - 100 / 3 - 10
Temperature (supply 12°C)	°C	min. 80 - max. 155
Power rating	kW	3.4
Consumption fuel oil	kg/h	4.6
Heating oil consumption, ecolefficiency	kg/h	3.7
Power cable	m	5
Fuel tank	1	25
Weight (with accessories)	kg	159.3
Weight incl. packaging	kg	171.3
Dimensions (L × W × H)	mm	1330 × 750 × 1060

This device requires instruction.

Environment		
Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10 / Longlife
Spray lance	mm	1050
Power nozzle		
ANTI!Twist		
Tanks for detergent, scale inhibitor and fuel can be filled from outside		•
Control panel with indicator lamps		
Pressure switch control		
Electronic service control with LED display		•
Two detergent tanks		•
Dry running protection		
■ Included in delivery.		

HDS 7/10-4 M, 1.077-901.0, 2023-01-20






Efficiency

- In the Eco setting the unit operates in the most economical temperature range (60°C) with full water flow.
- Burner cycles are optimised to reduce fuel consumption by up to 20% compared to full-load operation.



Maximum efficiency

- Highly efficient burner technology.
- 4-pole, slow-running electric motor guarantees a long working time.



Operational reliability

- The large, integrated fine-mesh water filter reliably protects the high-pressure pump against dirt particles.
- An integrated exhaust gas thermostat switches off the drive motor if the exhaust gas temperature exceeds 300°C.
- The soft damping system (SDS) compensates for vibrations and pressure surges in the high-pressure system.



























14

		Order no.	Description	
TRIGGER GUNS		order no.	Description	_
Trigger guns				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	ŀ
Conversion kit 1 from high pressure hose	2	4.111-050.0	A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.	
Conversion kit 2 from device	3	4.111-051.0	Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.	
Conversion kit 3 only EASY!Force	4	4.111-052.0	A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.	
Servo Control				
Servo Control, 750 l/h - 1100 l/h	5	4.118-008.0	Water quantity and pressure regulated directly from the hand spray gun.	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	•
LED nozzle light	7	2.680-002.0	LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.	
Spray lance, 250 mm, rotatable	8	4.112-027.0	250 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 400 mm, rotatable	9	4.112-024.0	400 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 600 mm, rotatable	10	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	11	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	12	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	13	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	

 $[\]blacksquare$ Included in delivery. $\hfill\Box$ Available accessories.























		Order no.	Description	
SPRAY LANCES				
Double lance		ı		
Double lance, 960 mm	15	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance				
WC and gutter lance	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140° , ideal for cleaning difficult to reach areas, e.g. gutters.	[
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	[
Gutter cleaner				
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	1 [
Undercarriage spray lance	•			
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	[
KÄRCHER POWER NOZZLE		1		Ť
Power nozzle spray angle 25°				Т
Power Nozzle , 054	22	2.113-011.0	Flat jet nozzle for large area performance and stubborn dirt.	
HP nozzle spray angle 0°		•		Ť
Power Nozzle 0°, 055	23	2.113-035.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	[
Power nozzle spray angle 15°		'		
Power Nozzle 15°, 055	24	2.113-047.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	[
Power nozzle spray angle 40°				Ī
Power Nozzle 40°, 055	25	2.113-055.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 10 m, DN 8, 400 bar, 2 \times EASY!Lock	26	6.110-038.0	Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressure.	
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 \times EASY!Lock	27	6.110-024.0	1.5 m high-pressure hose (DN 8, M 22×1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5).	
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 × EASY!Lock	28	6.110-023.0	With rotary coupling, $2 \times M$ 22×1.5	I



EQUIPMENT FOR HDS 7/10-4 M 1.077-901.0













		Order no.	Description	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 20 m, DN 8, 400 bar, $2 \times EASY!Lock$	29	6.110-027.0	with rotary coupling, 2 \times M 22 \times 1.5	
High-pressure hose Longlife, 15 m, DN 8, 400 bar, 2 × EASY!Lock	30	6.110-029.0	With rotary coupling, 2 \times M 22 \times 1.5	
Standard with unions on both sides				
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	31	6.110-031.0	10 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	32	6.110-030.0	15 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	33	6.110-032.0	20 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	34	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	35	6.110-042.0	15 m high-pressure hose M 22 \times 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155 $^{\circ}$ C/220 bar.	
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	36	6.110-043.0	with union on both sides, M 22×1.5 with anti-kink protection. NW $10/155^{\circ}$ C/220 bar	
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	37	6.110-044.0		
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	38	6.110-045.0		
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	39	6.110-059.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides, $2x M 22 \times 1.5$ with anti-kink protection.	
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	40	6.110-060.0		
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	41	6.110-041.0		
Food industry version with unions on both side	25			_
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	42	6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22×1.5 with anti-kink sleeve.	

 \blacksquare Included in delivery. \qed Available accessories.

























		Order no.	Description	
HIGH-PRESSURE HOSES				
Food industry version with unions on both side	es			L.
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	43	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 × 1.5, with kink protection. NW 8/155°C/250 bar.	
Longlife food industry version with unions on	both s	ides		
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	44	6.110-053.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, $2 \times M$ 22×1.5	
STROMGENERATOR				
PGG 6/1	45	1.042-208.0		[
WEED CONTROL				
WR 50	46	2.114-013.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	r.
WR 20	47	2.114-014.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	[
WR 100	48	2.114-015.0	For thorough weed removal: The WR 100 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 100 cm wide nozzle bar and nozzle adapter.	
WR 10	49	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	
QUICK CONNECT				
Quick-fitting pipe union coupler trapezo	50	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	[
Quick-fitting pipe union plug nipple tra	51	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22×1.5 external thread.	[
DRUM AND TANK CLEANING				
Add-on kit mud sucker	52	2.641-798.0		[
OTHER HP ACCESSORIES				
Jet gun	53	2.869-067.0	Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.] [
FLUE PIPE				
Flue gas adapter	54	4.656-149.0	Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for	[
	55	4.656-080.0	connection to a stack system).	[
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				
Dirt Blaster Nozzle, large, 055/060	56	4.114-036.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzland bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	le l

[☐] Available accessories.





















	1			\top
		Order no.	Description	
MULTIPLE-JET NOZZLES		<u>'</u>		
Angle vario nozzle 0°-90°				
Angled Vario Nozzle, 055	57	4.113-008.0	Variable angle nozzle for spray angle adjustment from 0° to 90° . For easy adjustment to all kinds o soiling and surfaces.	f [
STEAM NOZZLE / NOZZLE PROTECTOR / ROLLO	OVER N	OZZLE		
Steam nozzle				
Steam jet nozzle 50°	58	4.116-000.0	Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.	
Steam jet nozzle 40°, 055	59	2.114-003.0	Brass steam nozzle for operation of the HDS in steam stage.	
NOZZLE UNION / SPACER		<u> </u>		
Nozzle union				
Nozzle screws	60	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
PIPE CLEANING		<u> </u>		
Pipe cleaning hose, ID 6				
Hose assembly TR pipe cleaning DN6 max.2	61	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, 220 bar	62	6.110-008.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R $1/8$ nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	63	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle		•		
Dirt blaster pipe cleaning D21/060	64	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Dirt blaster pipe cleaning D30/060	65	4.765-005.0	jets ensure the necessary forward movement, as well as convenient handling.	
Nozzle pipe cleaning size 80	66	5.763-087.0	Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	
Nozzle pipe cleaning size 120	67	5.763-089.0	Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	68	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	Е
	69	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	70	5.763-021.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	

[☐] Available accessories.





























		Order no.	Description	
PIPE CLEANING				
Pipe cleaning nozzle				
Rotating pipe cleaning nozzle	71	6.415-428.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Add-on kit hose attachment	72	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	[
Add-on kit dirt trap	73	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	[
Hard surface cleaner FR 30 ME				
FR 30 ME surface cleaner	74	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50				
FR 50 surface cleaner	75	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosin system.	g
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 650 l/h - 850 l/h	76	2.639-187.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (650 to 850 l/h).	
Machine-specific nozzle kits for FRV		'		
Nozzle kit for FRV, 080	77	2.642-982.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	[
Hard surface cleaner FRV 30 Me	•			
Extension hose FRV 30 Me and FRV 50 Me	78	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	[
FRV 30 Me Surface Cleaner	79	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Basic 2, 700 l/h - 800 l/h	80	4.112-054.0	For high-pressure cleaners with a flow rate of 700-800 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
1-litre cleaning agent container for cup foam lance basic	81	5.071-414.0		[
1-litre cleaning agent container for cup foam lance advanced	82	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	[
Cup foam lance Advanced 2, 700 l/h - 800 l/h	83	4.112-064.0		[
Cup foam lance DUO Advanced 2, 700 l/h - 800 l/h	84	4.112-068.0		[
Available accessories				

[☐] Available accessories.



























				_
		Order no.	Description	
FOAM SYSTEMS				
Inno Foam Set				
Inno foam kit with detergent injector	85	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or	
Inno foam kit	86	2.112-008.0	disinfection.	[
Easy Foam Set				
Easy Foam Set with RM injector	87	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine	
Easy foam set	88	2.112-011.0	specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 090 Inno/Easy kit 700 - 1000 I/h	89	2.111-019.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.	
Foam nozzle mounting kit	1			
Foam nozzle kit	90	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	[
MIXERS AND INJECTORS		<u> </u>		_
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	91	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	92	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	[
Machine-specific nozzle kit with order no. 3.63	37-170)		
Nozzle insert trapezoidal thread HDS-GER	93	4.769-011.0	For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-001		•		
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	94	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	95	4.769-001.0	For low pressure with machines up to 1.100 l/h	[
COUPLING PARTS				Ė
Rotary coupling				
Rotary coupling	96	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	[
Connector	•	,		
Nozzle connector/screw connector	97	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times M 22 \times 1.5$ and $1 \times M 18 \times 1.5$.	
Y distributor	98	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	[

 $[\]hfill \square$ Available accessories.





























	_			_
		Order no.	Description	
COUPLING PARTS				
Connector				
Short spray unit	99	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	: □
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	100	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	101	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	102	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 - Swivel	103	4.111-032.0	M22 \times 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	104	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	105	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	106	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	107	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Coupler -2xM22x1,5	108	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$.	
ADAPTER for replacement TR22IG-M22AG Er	109	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$	110	2.639-257.0		
Automatic hose reel, powder-coated steel / plastic, 20 m	111	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	112	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	

 $[\]hfill \square$ Available accessories.



























		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic hose reel, coated, 20 m	113	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	. [
Hose reel, automatic, basalt grey-coated, 20 m	114	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	115	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	116	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	117	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120° . Galvanised steel.	
Stainless steel swivel holder	118	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	
Anbausatz Schlauchtrommel automatik		•		
Attachment kit automatic hose reel HDS M/S	119	2.110-011.0	Automatic hose reel as a complete attachment kit that's easy to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose.	
Attachment kit automatic hose reel holder HDS M/S	120	2.110-020.0	Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes.	
FACADE AND SOLAR PANEL CLEANING				Ť
Brushes				
Drive for roller brush 500	121	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	122	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	123	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0), Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roller brush 500 medium	124	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	125	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	126	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	

[☐] Available accessories.





















		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING		order no.	Description	_
Brushes				_
Brush medium	127	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush soft	128	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	[
Telescopic		•		
TL low pressure adapter	129	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	130	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	131	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. [
Telescopic lance TL 10 H	132	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	[
Telescopic lance TL 10 C	133	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	[
Telescopic lance TL 14 C	134	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	135	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	136	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	137	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	[
Nozzle pack for wet blasting attachment				
Nozzle pack TR wet jet set 0050	138	2.112-023.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment .	
Boron carbide nozzle				
Boron carbide nozzle, for machines as of 1000 l/h	139	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
DRUM AND TANK CLEANING				
Barrel and tank cleaning				
Barrel cleaner BC 14/12	140	2.112-020.0	The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums – in particular oak barrels with a capacity between 225 and 600 liters.	

[☐] Available accessories.

























			Description	
		Order no.		
DRUM AND TANK CLEANING				Ť
HKF 50 spray head, brass				Г
HKF 50 spray head, brass	141	3.631-058.0	Interior cleaning head for barrels and containers with bungholes of 50 mm and more.	-
Nozzle kit for HKF 50 spray head (3.631-009.0	/ 3.63	31-039.0)		Ť
Nozzle 090 for single nozzle operation HKF 50	142	6.415-447.0	Nozzle for single-nozzle operation	
Double handle for exact control of the spray head	143	2.863-036.0	Double handle. Precise control of the spray head	[
Screw plug for using a spray head with one nozzle	144	5.411-061.0	Screw plug for using a spray head with one nozzle	[
ADD-ON KITS		·		
Crane lifting kit				
Transport eyelet attachment kit	145	2.644-053.0	Robust transport eyelet attachment kit for the secure fixing of HDS Medium and Super Class pressure washers during transport.	[
Flame monitoring attachment kit				
ABS flame monitor for HDS M/S	146	2.641-796.0	More safety thanks to ABS HDS M/S flame monitoring system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.	[
Accumulator kits				
Add-on accumulator for HDS M/S	147	2.641-803.0	The accumulator can be mounted on the HDS machine in order to dampen pressure surges, which conserves the machine's line system.	[
Remote control set				
Remote control set	148	2.642-157.0	Remote control for the machines of the HDS Middle and Super class with the functions on/off, hot/cold water and cleaning agent on/off. For mounting to a wall.	
Coin-op remote control				
Coin-op remote control	149	2.642-158.0	Retrofittable coin acceptor for machines in the HDS Middle and Super class for self-service operation. For installation on the machine.	[
WATER CONNECTION				
Geka coupling				Ļ
With hose nozzle, R 3/4"	150	6.388-455.0	with hose liner	[
With hose nozzle, R 1"	151	6.388-465.0	with hose barb	[
Hose coupling	152	6.388-458.0	with female thread	[
Suction filter				
Water filter	153	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μ m mesh, R 3/4" and R 1" connection, without non-return valve	1 [
Suction filter with check valve	154	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	[

[☐] Available accessories.



















		Order no.	Description	
WATER CONNECTION	<u> </u>			
Fine-mesh water filter				
Add-on kit water filter universal	155	2.637-020.0		
Fine-mesh water filter with adapter	156	4.730-102.0	Fine-mesh water filter, $125 \mu m$, max. temperature 50° C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h . Connection $3/4^{\circ}$, with adapter, 1° .	,
Fine-mesh water filter, 100 μ m, R 1"	157	2.638-270.0	Fine-mesh water filter, $100 \mu m$, max. temperature 60° C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$. Connector 1".	; 🗆
Water supply hose				
Water supply hose	158	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C	
	159	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
Backflow check valve		•		
Backflow preventer	160	2.641-374.0	To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. – hot water resistant up to 80 °C – tested according to IEC 60335-2-79 – integrated leakage protection	
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush, M 18 × 1.5	161	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.	
Rotating washing brush		•		
Rotating wash brush for < 800 l/h machines, nylon bristles	162	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60° C. (M 18×1.5 , replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	163	4.113-003.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18×1.5 (replaceable brush insert).	

 $[\]hfill\square$ Available accessories.