



Compact 48 litre wet & dry multi-purpose vacuum



#### Order no.

#### 1.428-622.0

490 × 390 × 780

All-purpose brush

Dimensions (L × W × H)

Cartridge filter with larger filter area

#### Drain hose

#### Technical data EAN code 4039784724952 V/Hz 220 - 240 / 50 - 60 Current type Air flow l/s 67 Vacuum mbar / kPa 200 / 20 **Container content** L 48 Plastic **Container material** Rated input power w max. 1380 ID 35 Standard nominal size Cable length 7.5 m Sound pressure level dB(A) 72 Weight without accessories 10.5 kg

mm

Suction hose	m	2.5 / with bend
Suction Tube	Piece(s) × m	2 × 0.5 / Metal
Filter bag	Piece(s)	1 / Paper
Wet and dry floor tool	mm	400
Crevice nozzle		
Cartridge filter		-
Drain hose		
Safety class		II
Caster with brake		
Included in delivery.		





**Container emptying** 

Accessory storage

- Easily accessible drain hose for convenient liquid disposal.
- Accessories can be attached to the container at the rear of the machine.

EQUIPMENT FOR NT 48/1

1.428-622.0

1 2-3	4			
9				
		Order no.	Description	
CARTRIDGE FILTER, STANDARD, BIA C	OR UP TO DUS	T CLASS M		
Cartridge filter paper Cartridge filter	1	6.414-789.0	Paper cartridge filter with larger filter surface, standard for NT 48/1 and optional for NT 27/1/Me Advanced.	
BENDS				
Plastic bend				
Plastic bend	2	5.031-718.0	Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	
	3	5.031-939.0	Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	
Plastic bend, ID 35	4	6.902-009.0	Plastic, ID 35.	
Bend metal				
Bend, DN 35, metal	5		Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0, C 35-DN 35, plastic, el.).	
Bend, stainless steel ID 35	6	6.903-141.0	Stainless steel and crooked, ID 35	
SUCTION NOZZLES				
All-purpose brushes		1		
All-purpose brush	7		All-purpose brush PPN_Bristle	
	8	6.903-863.0	Natural bristles (ox hair), bristle element 120 × 45 mm.	
All-purpose nozzles (wet/dry)		1		
Floor tool DN35	9		All-purpose plastic nozzle (DN 35) with 300 mm working width. With side rollers, brush strips (6.903-278.0) and squeegees (6.903-277.0). Only for NT vacuum cleaners.	
Wet and dry floor nozzle	10	2.889-118.0	Multi-purpose nozzle (DN 35) for wet vacuum cleaning of large areas. Squeegee and brush are quick and easy to change.	
Floor tool neutrally DN35	11	6.906-384.0	All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	
Crevice nozzles				
Crevice nozzle DN35	12	6.900-385.0	Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	
Crevice nozzle	13	6.900-922.0	Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	
Crevice nozzle DN40	14	6.903-033.0	Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	

**EQUIPMENT FOR NT 48/1** 1.428-622.0

12, 15	16	17	18	19	20-21	22
23	24	25	26	27	28	

				Т
		Order no.	Description	
SUCTION NOZZLES		order no.		_
Crevice nozzles				-
Crevice nozzle DN35	15	6.906-240.0	Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 250 mm.	
Car cleaning nozzles				
Car nozzle DN35	16	6.906-108.0	Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	
Car nozzle packaged with Signet	17	2.889-356.0		C
Rubber suction tools, nose 45°				
Rubber suction tools, nose 45°	18	6.902-104.0	45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	
Combi-nozzles (dry)				
Combination floor tool (dry)	19	6.906-511.0	Combination floor tool with changeover function, plastic (272 mm). With stainless steel base plate, thread catcher 6.905-417.0 and DN 35 connection.	
Pipe dusting nozzles				
BRUSH	20	6.903-035.0	Plastic, pipe diameter 100 mm	
	21	6.903-036.0	Plastic, pipe diameter 200 mm	E
Suction brushes				
Suction brush DN35	22	6.903-862.0	Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.	
Turbo nozzle				
Upholstery nozzle TURBO	23	2.860-113.0	Plastic turbo upholstery nozzle (DN 35/32, 160 mm) with reduction sleeve.	
Floor tool TURBO DN 35/32	24	2.860-114.0	Plastic turbo floor nozzle (DN 35/32, 270 mm) with reduction sleeve.	E
SUCTION TUBES				
Suction tubes metal				
Suction tube DN35	25	6.900-514.0	Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	
Suction tubes stainless steel				
Suction tube, DN 35	26	6.902-154.0	0.5 m long stainless steel suction tube (ID 35) for wet and dry vacuum cleaners. Ideal for frequent wet vacuuming applications and for vacuuming corrosive components.	
Suction tubes plastic			•	
Suction tube, DN 35	27	6.900-384.0	Plastic suction tube (DN 35, 1x0.5 m) only suitable for BV and T vacuum cleaners.	
SUCTION HOSES				
Suction hoses with clip system 1.0 (com	patible with	vacuum cleane	ers up to model year 2016)	
Suction hose C DN35	28	4.440-626.0	2.5 m standard suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory end. Without PDFC module. Standard for NT 27/1/Me Advance und NT 48/1.	ľ

# EQUIPMENT FOR NT 48/1 1.428-622.0

29, 33 29, 33				$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array}\\ \left\begin{array}{c} \end{array}\\ \end{array}\\ \end{array}\\ \end{array}\\ \left\begin{array}{c} \end{array}\\ \end{array}\\ \end{array}\\ \end{array}\\ \left\begin{array}{c} \end{array}\\ \end{array}\\ \end{array}\\ \left\begin{array}{c} \end{array}\\ \end{array}\\ \end{array}\\ \left\begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \end{array}\\ \left( \begin{array}{c} \end{array}\\ \end{array}\\ \left( \begin{array}{c} \end{array}\\ \end{array}\\ \left( \begin{array}{c} \end{array}\\ \end{array}\right)}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \end{array}\right)}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \end{array}\right)}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\right)}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array}\right)}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array}\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})}\\ \left( \begin{array}{c} \end{array})\\ \left( \begin{array}{c} \end{array})}\\ \left( \end{array})\\ \left( \end{array})$ \left( \end{array}) \left) \left( \end{array}) \left( \end{array}) \left( \end{array}) \left( \end{array}) \left( \end{array}) \left) \left( \end{array}) \left( \end{array}) \left( \end{array}) \left) \left( \\) \left( \end{array}) \left( \\) \left( \end{array}) \left( \\) \left( \end{array}) \left) \left( \\) \left( \\) \left( \end{array}) \left) \left( \\)
			Order no.	Description
SUCTION HOSES				
				ers up to model year 2016)
Extension hose, C 32, C 3	35 clip system	29	6.906-237.0	Electrically non-conductive standard extension hose for all C-32 and C-35 hoses with clip system.
Suction hose		30	6.906-241.0	4 m suction hose without bend and adapter. With bayonet at vacuum end and C 35 clip connection $\hfill\square$ at accessory end. $\hfill\square$
		31	4.440-653.0	2.5 m electrically conductive suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory end. Without module.
		32	6.906-275.0	2.5 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.
			1	and c 55 cmp connection at accessory cna.

	32	6.906-275.0	2.5 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.	
Extension hose, C 40	33	6.906-344.0	2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	
Suction hose (clip system), C 35, el.	34	6.906-500.0	4 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.	
Suction hose	35	6.906-714.0	With bayonet and clip connection.	
Suction hose electrically conducting C40	36	6.907-363.0	Electroconductive suction hose, NW 35. Length: 4 metres.	
Repair kits				
Repair set, C 35	37	2.639-682.0	Repair set (C35) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	
Hose connection				
Adapter, DN 32/35, with internal thread	38	6.902-077.0	Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	C 🗆
Suction hoses with cone connection				
Suction hose, complete	39	4.440-287.0	Standard, 4.0m, ID 35	
	40	4.440-263.0	Electrically non-conductive 4.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	
Suction hose complete, ID 40, 4 m, oil-resistant,	41	4.440-303.0	Oil-resistant.	
Suction hoses with distinctive connection for	Zone 2	2		

# **EQUIPMENT FOR NT 48/1**

1.428-622.0

	5		$\begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 &$	
SUCTION HOSES		Order no.	Description	
Suction hoses others				
Suction hose, complete	43	4.440-461.0	Electrically non-conductive suction hose (7 m) with DN 27 power tool adapter at accessory end and DN 27 bayonet at vacuum end. Connectors available on request.	
NOZZLE SETS				
Nozzles set DN35	44	2.860-116.0	Nozzle kit for all NT vacuum cleaners with DN 35 accessories includes crevice tool, upholstery tool, round brush $(x3)$	
OTHER ACCESSORIES FOR T AND NT				
Drilling dust tool	45	2.679-000.0	Drilling dust nozzle for dust-free vacuuming. Suitable for dry and wet and dry vacuum cleaners from Kårcher.	
CS 40 Me	46	2.863-026.0	The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	
FILTER BAGS				
Paper filter bags		1		
Paper filter bags, 5 × , NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC	47	6.904-285.0	5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	
FILTER T/ NT				
Special filter bags, wet filter bags				
Filter bag 5St. Kae.	48	6.904-211.0	Tear-resistant special/wet filter bag for dust class L, suitable for dry and wet pick up. Suitable for NT 561, NT 611 and NT 611 K.	
Membrane filter / fabric filter		6 005 100 5		
Membrane filter, NT 27/1, NT 48/1, NT 351	49	6.906-103.0	Polyester needle fleece membrane/fabric filter, washable up to 40°C. For NT 27/1/Me Advance, NT 48/1, NT 351 Eco/Professional.	
CONNECTING SLEEVES	hu a - :	n elu esti u = `		
Connecting sleeve C-DN (clip on taper), EL (elec			Connects C 35 hose for ID 35, electrically conductive.	
Adapter for electric power tools, clip on, el.	50	5.407-112.0	בטווופנוג כ גם ווטצ וטו ום בס, פפננוונמווץ נטוומטנוועפ.	
Sleeve for tool C35EL	51	5.453-042.0	3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	
Adapter for electric power tools, C 35, el.	52	5.453-048.0	Inner Ø 25.4 mm, outer Ø 34.6 mm/ 38 mm, el. Only NT-vacuums.	
	53	5.453-050.0	Inner Ø 27 mm, outer Ø 36.5 mm/ 38.8 mm, el. Only NT-vacuums.	
Adapter for electric power tools, screwable		1		
Power tool adapter, threaded, DN 35	54	5.453-016.0	3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	
Adapter for electric power tools, screwable, ID 35	55	5.453-026.0	Inner Ø 28.6 mm, outer Ø 37.3/38.8 mm.	
Power tool adapter, threaded, DN 35	56	6.902-059.0	Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.	



EQUIPMENT FOR NT 48/1 1.428-622.0



		Order no.	Description	
CONNECTING SLEEVES				
Adapter for electric power tools, screwable				
Power tool adapter, threaded, DN 35	57	6.902-095.0	2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm.External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.	
Reducer (tube -> nozzle)		•		
Reducer from ID 35 to 32	58	6.902-072.0	Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	
Set reducing / extension sleeves		•		
Set reducing / extension sleeves	59	2.860-117.0	ID 40/35, ID 35/32 (tube -> nozzle), plastic.	

□ Available accessories.